

KRÜSS

Ayríis

Specifications



Product group specifications**Ayríis****Camera system**

Type	stereo camera
Connection	MIPI CSI-2
Performance	2 cameras with 50 fps at 1024 x 1024 px each

Optics

Focus	fixed focus
Zoom	fixed focal length

Illumination

Type	2 lasers + 90 high power LEDs
Wave length, dominant	white

Dosing system

Dosing	water single pressure dosing
Drop deposition	software-controlled
Cartridge (volume)	prefilled water cartridge (4 mL)
Resolution	0.1 μ L
Speed	fixed

Output

Type	Microsoft Excel (xml format) via Ethernet
------	---

Measurement specifications**Ayríis****Sessile drop**

Result	contact angle
Models	3D contact angle
Type	static

Software

Software type	integrated user interface
Available software modules	contact angle

General specifications

Ayríís

Sample dimensions

Maximum sample size $\infty \times \infty \times \infty$ (W x D x H)

Housing and peripherals

Compartment aluminum
Touch display "integrated color IPS display
(480 x 800 px, size 4")"

Environment

Operating temperature 10 °C to 40 °C
Storage temperature 5 °C to 45 °C
Humidity without condensation

Instrument dimensions

Footprint 58 mm x 51 mm (W x D)
Height 290 mm
Weight (without accessories) 1.15 kg

Power supply

Voltage 15 V
Battery runtime 4 h
Charging power max. 30 W

Interfaces

PC USB 3.0

